


## SUITABILITY AREA PRODUCT & COMPOSITION GUIDE

Reference	Wall	Floor	Wet areas	Pools	Material
All Products	INT/ EXT	RESIDENTIAL	YES	YES	GLASS

## TECHNICAL CHARACTERISTICS

Test UNE-EN-ISO 10545-3 Water Absorption	Test UNE-EN-ISO-101-92=101 Surface hardness. Mosh.	Test UNE-EN-ISO 10545-9 Resistance to thermal shocks	Test UNE-EN-ISO 10545-12 Frost Resistance	Test UNE-EN-ISO 10545-13:1998 Resistance to chemical attack			
				Domestic products	Pool water additives	Low Acid and alkalins	High Acid and alkalins
None	4	Resistant	Resistant	GA	GA	GLA	GHA
Test UNE-EN-ISO 10545-14 Resistance to staining	Test UNE-EN-ISO 10545-11=1997 Cracking	DIN 51094 Colour Stability on exposure to light and UV rays	ASTM C-1028-96		DIN 51130:2004 SLIP Resistance wearing shoes	DIN 51097 SLIP resistance in bare feet	Test UNE-ENV 12633:2003 (CTE) anti skid coefficient, suitable for outdoor use and swimming pools
			Friction dry coefficient	Friction wet coefficient			
Class 5	Resistant	Resistant					

## PACKING

SHEET HOJA	BOX CAJA	PALLET PALET	EURO PALLET EURO PALET
 size / dimensión: 311x311 mm (12.24"x12.24")	sheets / hojas: 5	quantity / cantidad: 105,84 m <sup>2</sup> (1,139 sqft)	quantity / cantidad: 70,56 m <sup>2</sup> (759.5 sqft)
 thickness / espesor: 4,9 mm (0.19")	quantity / cantidad: 0,49 m <sup>2</sup> (5.27 sqft)	boxes / cajas: 216	boxes / cajas: 144
 weight / peso: 0,91 Kg (2.01 lb)	weight / peso: 4,57 kg (10.1 lb)	gross weight / peso bruto: 987,12 kg (2,175 lb)	gross weight / peso bruto: 658 Kg (1,450 lb)