



Variation of colour and design
V₂
Structure: No

GRES SP



Catalogue N°	6422	6423	6421
EAN-13 Code	3800745642216	3800745642315	3800745642117
Description	Gres SP 7 mm Beige	Gres SP 7 mm Mid Grey	Gres SP 7 mm Anthracite
Type	Unglazed Porcelain Tiles	Unglazed Porcelain Tiles	Unglazed Porcelain Tiles
Typology	FLOOR F/W	FLOOR F/W	FLOOR F/W
Size/cm	33.3x33.3	33.3x33.3	33.3x33.3
Color	BIEGE	MID GREY	ANTHRACITE
Surface	SATINATO	SATINATO	SATINATO
Unit of measurement	m ²	m ²	m ²
Number of tiles/box	15	15	15
Sq.m./box	1.66	1.66	1.66
Number of boxes/pallet	44	44	44
Sq.m./pallet	73.19	73.19	73.19
Gross Kg/pallet approx.	1105	1105	1105
Thickness/mm	7	7	7
Manufacturer	KAI	KAI	KAI



***Colour reproduction approximate**

Colour reproduction approximate. The tables with data referred to the content per box and to the packing weight are update at the catalogue printing time; therefore the listed data can be altered.

KAI Group have the exclusiv right to modify and replace the components of the system illustrated in this folder, even only partially and with no obligation to give prior notice there of.



Digital Technology



V₁ Plain colour&design



V₂ Slight variation of colour&design



V₃ Medium variation of colour&design



V₄ Intensive variation of colour&design

A degree of colour or shade variation is an inherent part of these products.

Please ensure that a satisfactory effect can be reached prior to installing the products. Carefully check the tiles for any defects prior to fixing. Claims after fixing of the tiles are not accepted. In one box may be found color, relief and other variation of different patterns and tile's faces on the same design to provide natural appearance. It is strongly recommended to visit the Web site of the manufacturer of the tiles or to require the tiling masters to check the user's guide of the manufacturer before using the products. The use of appropriate waterproof joints and adhesives for fixing of the tiles is of high importance. Make sure your surface is even and clean before fixing the tiles. It is recommended the space between the tiles (the joints) to be at least 3mm. After fixing the tiles wait until the adhesives have dried completely and afterwards proceed with the joints in order not to seal the moisture within. Use for fixing of the tiles waterproof materials and always lay in advance waterproofing! Always keep a tile and a packaging of the products used as a reference in case of a customer's complaint.



Floor



Wall



Porcelain



Matt



Glossy



Special effect



Rectified



Lappato



Structure



Smart Surface



60x120, 60x60 and 30x60 rectified sizes can be used in modular combinations if laid with 2 mm joint.