

SUITABILITY AREA PRODUCT & COMPOSITION GUIDE

Reference	Wall	Floor	Wet areas	Pools	Material
ALL PRODUCTS	INT/ EXT	NO	YES	YES	GLASS

TECHNICAL CHARACTERISTICS

Test UNE-EN-ISO 10545-3 Water Absorption	Test UNE-EN-ISO-101-92=101 Surface hardness. Mosh.	Test UNE-EN-ISO 10545-9 Resistance to thermal shocks	Test UNE-EN-ISO 10545-12 Frost Resistance	Test UNE-EN-ISO 10545-13:1998 Resistance to chemical attack			
				Domestic products	Pool water additives	Low Acid and alkalins	High Acid and alkalins
None	4	Resistant	Resistant	GA	GA	GLA	GHA
Test UNE-EN-ISO 10545-14 Resistance to staining	Test UNE-EN-ISO 10545- 11=1997 Cracking	DIN 51094 Colour Stability on exposure to light and UV rays	ASTM C-1028-96		DIN 51130:2004 SLIP Resistance wearing shoes	DIN 51097 SLIP resistance in bare feet	Test UNE-ENV 12633:2003 (CTE) anti skid coefficient, suitable for outdoor use and swimming pools
			Friction dry coefficient	Friction wet coefficient			
Class 5	Resistant	Resistant					

PACKING

SHEET HOJA



size / dimensión:
311x311 mm (12.24"x12.24")



thickness / espesor:
4,9 mm (0.19")



weight / peso:
0,91 Kg (2.01 lb)

BOX CAJA

sheets / hojas:
10

quantity / cantidad:
0,98 m² (10.55 sqft)

weight / peso:
9,14 kg (20.14 lb)

PALLET PALET

quantity / cantidad:
121,80 m² (1,311 sqft)

boxes / cajas:
126

gross weight / peso bruto:
1151,6 kg (2,538 lb)

EURO PALLET EURO PALET

quantity / cantidad:
82,32 m² (886.1 sqft)

boxes / cajas:
84

gross weight / peso bruto:
767,76 Kg (1,692 lb)