

SUITABILITY AREA PRODUCT & COMPOSITION GUIDE

Reference	Wall	Floor	Wet areas	Pools	Material
All Products	INT/ EXT	RESIDENTIAL	YES	YES	GLASS

TECHNICAL CHARACTERISTICS

Test UNE-EN-ISO 10545-3 Water Absorption	Test UNE-EN-ISO-101-92=101 Surface hardness. Mosh.	Test UNE-EN-ISO 10545-9 Resistance to thermal shocks	Test UNE-EN-ISO 10545-12 Frost Resistance	Test UNE-EN-ISO 10545-13:1998 Resistance to chemical attack			
				Domestic products	Pool water additives	Low Acid and alkalins	High Acid and alkalins
None	4	Resistant	Resistant	GA			
Test UNE-EN-ISO 10545-14 Resistance to staining	Test UNE-EN-ISO 10545- 11=1997 Cracking	DIN 51094 Colour Stability on exposure to light and UV rays	ASTM C-1028-96		DIN 51130:2004 SLIP Resistance wearing shoes	DIN 51097 SLIP resistance in bare feet	Test UNE-ENV 12633:2003 (CTE) anti skid coefficient, suitable for outdoor use and swimming pools
			Friction dry coefficient	Friction wet coefficient			
Class 5	Resistant	Resistant					

PACKING

SHEET HOJA



size / dimensión:
311x311 mm (12.24"x12.24")



thickness / espesor:
4,9 mm (0.19")



weight / peso:
0,91 Kg (2.01 lb)

BOX CAJA

sheets / hojas:
5

quantity / cantidad:
0,49 m² (5.27 sqft)

weight / peso:
4,57 kg (10.1 lb)

PALLET PALET

quantity / cantidad:
105,84 m² (1,139 sqft)

boxes / cajas:
216

gross weight / peso bruto:
987,12 kg (2,175 lb)

EURO PALLET EURO PALET

quantity / cantidad:
70,56 m² (759.5 sqft)

boxes / cajas:
144

gross weight / peso bruto:
658 Kg (1,450 lb)